

## Easy Re-Order Sheet For Your Eagle 4 Barcode Printer



### Thermal Transfer Ribbon Rating Scale: 1 = lowest performance, 5 = highest performance

Width/Length	Part Number	Formulation	Uncoated Paper	Coated Paper	Synthetics	Polys	Kimdura	Styrene
2.09"/1968'	CEB053600TE	Wax/Resin	2	4	4	4		
2.99"/1968'	CEB076600TE	Wax/Resin	2	4	4	4		
3.50"/1968'	CEB089600TE	Wax/Resin	2	4	4	4		
4.17"/1968'	CEB106600TE	Wax/Resin	2	4	4	4		
4.49"/1968'	CEB114600TE	Wax/Resin	2	4	4	4		
5.16"/1968'	CEB131600TE	Wax/Resin	2	4	4	4		
2.09"/1969'	CE1100052600L	Wax(resin enhanced)		3				
3.00"/1969'	CE1100076600L	Wax(resin enhanced)		3				
3.50"/1969'	CE1100089600L	Wax(resin enhanced)		3				
4.17"/1969'	CE1100106600L	Wax(resin enhanced)		3				
4.49"/1969'	CE1100114600L	Wax(resin enhanced)		3				
5.16"/1969'	CE1100131600L	Wax(resin enhanced)		3				
1.57"/1969'	CE2100040600TE	Wax/Resin	3	4	3	3	2	1
2.09"/1969'	CE2100053600TE	Wax/Resin	3	4	3	3	2	1
2.52"/1969'	CE2100064600TE	Wax/Resin	3	4	3	3	2	1
2.52"/1969'	CE2100064600TEA	Wax/Resin	3	4	3	3	2	1
3.00"/1969'	CE2100076600TE	Wax/Resin	3	4	3	3	2	1
3.50"/1969'	CE2100089600TE	Wax/Resin	3	4	3	3	2	1
4.00"/1969'	CE2100101600TE	Wax/Resin	3	4	3	3	2	1
4.17"/1969'	CE2100106600TE	Wax/Resin	3	4	3	3	2	1
4.17"/1969'	CE2100106600TEA	Wax/Resin	3	4	3	3	2	1
4.50"/1969'	CE2100114600TE	Wax/Resin	3	4	3	3	2	1
5.12"/1969'	CE2100130600TE	Wax/Resin	3	4	3	3	2	1
2.99"/1968'	CH076600TE	Wax	2	3				
4.17"/1968'	CH106600TE	Wax	2	3				
5.16"/1968'	CH131600TE	Wax	2	3				
2.99"/1968'	EAGLE76	Wax/Resin	2	4	4	4	4	4
4.17"/1968'	EAGLE106	Wax/Resin	2	4	4	4	4	4
5.16"/1968'	EAGLE131	Wax/Resin	2	4	4	4	4	4
2.09"/1969'	CE3100053600TE	Resin			5	5	5	5
2.52"/1969'	CE3100064600TE	Resin			5	5	5	5
3.00"/1969'	CE3100076600TE	Resin			5	5	5	5
3.15"/1969'	CE3100080600TE	Resin			5	5	5	5
3.27"/1969'	CE3100083600TE	Resin			5	5	5	5
3.50"/1969'	CE3100089600TE	Resin			5	5	5	5
4.17"/1969'	CE3100106600TE	Resin			5	5	5	5
4.50"/1969'	CE3100114600TE	Resin			5	5	5	5
5.16"/1969'	CE3100131600TE	Resin			5	5	5	5

## Easy Re-Order Sheet For Your Eagle 4 Barcode Printer

(color & non-perforated labels also available)



### Thermal Labels TT = Thermal Transfer, DT = Direct Thermal

Media Type	Part Number	Width (in)	Length (in)	Labels/Roll	Qty/Case
TT - Perforated	CT150100P5500C3	1.5	1	5500	14
TT - Perforated	CT1501002P11000C3	1.5	1 (2 UP)	11000	6
TT - Perforated	CT200100P5500C3	2	1	5500	8
TT - Perforated	CT2001002P11000C3	2	1 (2 UP)	11000	4
TT - Perforated	CT200150P3500C3	2	1.5	3500	8
TT - Perforated	CT2001502P7000C3	2	1.5 (2 UP)	7000	4
TT - Perforated	CT200200P3000C3	2	2	3000	8
TT - Perforated	CT300100P5500C3	3	1	5500	8
TT - Perforated	CT300200P3000C3	3	2	3000	8
TT - Perforated	CT300300P2000C3	3	3	2000	8
TT - Perforated	CT300500P1200C3	3	5	1200	8
TT - Perforated	CT350100P5500C3	3.5	1	5500	4
TT - Perforated	CT350800P750C3	3.5	8	750	4
TT - Perforated	CT400100P5500C3	4	1	5500	4
TT - Perforated	CT400200P3000C3	4	2	3000	4
TT - Perforated	CT400250P2400C3	4	2.5	2400	4
TT - Perforated	CT400300P2000C3	4	3	2000	4
TT - Perforated	CT400400P1500C3	4	4	1500	4
TT - Perforated	CT400500P1200C3	4	5	1200	4
TT - Perforated	CT400600P1000C3	4	6	1000	4
TT - Perforated	CT400650P1000C3	4	6.5	1000	4
TT - Perforated	CT400800P750C3	4	8	750	4
TT - Perforated	CT4001200P500C3	4	12	500	4
TT - Perforated	CT4001300P500C3	4	13	500	4
TT - Perforated	CT500300P2000C3	5	3	2000	4
TT - Perforated	CT600400P1500C3	6	4	1500	4
TT - Fan-Folded	CT400200F6000C3	4	2	6000	2
TT - Fan-Folded	CT400300F4000C3	4	3	4000	2
TT - Fan-Folded	CT400600F2000C3	4	6	2000	2
TT - Fan-Folded	CT400650F2000C3	4	6.5	2000	2
DT - Perforated	CD300500P1200C3 (3" core)	3	5	1200	8
DT - Perforated	CD400200P3000C3 (3" core)	4	2	3000	4
DT - Perforated	CD400300P2000C3 (3" core)	4	3	2000	4
DT - Perforated	CD400400P1500C3 (3" core)	4	4	1500	4
DT - Perforated	CD400600P1000C3 (3" core)	4	6	1000	4
DT - Perforated	CD400650P1000C3 (3" core)	4	6.5	1000	4
DT - Fan-Folded	CD400600F2000C3	4	6	2000	2
DT - Premium Perforated	CD400200PP3000C3 (3" core, 8" OD wound out)	4	2	3000	4
DT - Premium Perforated	CD400600PP1000C3 (3" core, 8" OD wound out)	4	6	1000	4
DT - Premium Perforated	CD400650PP1000C3 (3" core, 8" OD wound out)	4	6.5	1000	4
DT - Premium Fan-Folded	CD400600PF2000C3	4	6	2000	2